



Feature

- 68V,88A
 $R_{DS\ (ON)} < 8.5 \text{ m}\Omega @ V_{GS}=10V$ TYP:6.5 mΩ
- Advanced Trench Technology
- Lead free product is acquired
- Excellent $R_{DS\ (ON)}$ and Good heat dissipation



Schematic Diagram



Marking and pin assignment

Application

- PWM applications
- Load Switch
- Power management

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity (PCS)
6888	AP6888	TO-220C	-	-	1000

ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	68	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($T_a = 25^\circ\text{C}$)	I_D	88	A
Continuous Drain Current ($T_a = 100^\circ\text{C}$)	I_D	54	A
Pulsed Drain Current ⁽¹⁾	I_{DM}	320	A
Singel Pulsed Avalanche Energy ⁽²⁾	E_{AS}	320	mJ
Power Dissipation	P_D	140	W
Thermal Resistance from Junction to Case	R_{eJC}	1.15	$^\circ\text{C}/\text{W}$
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55~+150	$^\circ\text{C}$

MOSFET ELECTRICAL CHARACTERISTICS($T_a=25^\circ C$ unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	68	-	-	V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 68V, V_{GS} = 0V$	-	-	1	μA
Gate-body leakage current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$	-	-	± 100	nA
Gate threshold voltage ⁽³⁾	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2	3	4	V
Drain-source on-resistance ⁽³⁾	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 40A$	-	6.5	8.5	$m\Omega$
Drain-source on-resistance ⁽³⁾	$R_{DS(on)}$	$V_{GS} = 6V, I_D = 30A$	-	8.3	11.5	$m\Omega$
Dynamic characteristics						
Input Capacitance	C_{iss}	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$	-	3600	-	pF
Output Capacitance	C_{oss}		-	320	-	
Reverse Transfer Capacitance	C_{rss}		-	300	-	
Switching characteristics						
Turn-on delay time	$t_{d(on)}$	$V_{DD}=35V, I_D=40A,$ $V_{GS}=10V, R_G=4.7\Omega$	-	20	-	ns
Turn-on rise time	t_r		-	52	-	
Turn-off delay time	$t_{d(off)}$		-	49	-	
Turn-off fall time	t_f		-	23	-	
Total Gate Charge	Q_g	$V_{DS}=35V, ID=40A,$ $V_{GS}=10V$	-	75	-	nC
Gate-Source Charge	Q_{gs}		-	26	-	
Gate-Drain Charge	Q_{gd}		-	20	-	
Source-Drain Diode characteristics						
Diode Forward voltage ⁽³⁾	V_{DS}	$V_{GS} = 0V, I_S = 30A$	-	-	1.2	V
Diode Forward current ⁽⁴⁾	I_S		-	-	88	A
Body Diode Reverse Recovery Time	trr	$T_J=25^\circ C, IF=20A, di/dt=100A/us$		23		ns
Body Diode Reverse Recovery Charge	Qrr	$T_J=25^\circ C, IF=20A, di/dt=100A/us$		16		nc

Notes:


1. Repetitive Rating: pulse width limited by maximum junction temperature
2. EAS Condition: $T_J=25^\circ C, V_{DD}=30V, R_G=25\Omega, L=0.5mH$
3. Pulse Test: pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
4. Surface Mounted on FR4 Board, $t \leq 10$ sec

Test Circuit


1) E_{AS} Test Circuits



2) Gate Charge Test Circuit:



3) Switch Time Test Circuit:



Typical Characteristics and Thermal Characteristics (Curves)




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 Rdson- Drain Current




Figure 4 Rdson-Junction Temperature




Figure 5 Gate Charge




Figure 6 Source- Drain Diode Forward




Figure 7 Capacitance vs Vds




Figure 8 Safe Operation Area




Figure 9 BVDS vs Junction Temperature




Figure 10 VGS(th) vs Junction Temperature





Figure 11 Normalized Maximum Transient Thermal Impedance

TO-220C Package Information



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.23		1.32	0.048		0.052
C3	2.20		2.60	0.087		0.102
D	8.90		9.90	0.350		0.390
E	9.90		10.3	0.390		0.406
F	6.30		6.90	0.248		0.272
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.39			0.133	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
Φ		3.6			0.142	